

**DreBon®**

**POWER TOOLS  
AIR TOOL**



**DreBon POWER TOOLS**

**PROFESSIONAL AIR TOOLS & ACCESSORIES**

POWER TOOL


**DB-I-30**



3/8" Air Impact Wrench  
(One Hammer)  
Max. Torque: 75 Ft-Lb

Square Drive	3/8"	
Capacity (Bolt Size)	3/8"	M 10
Free Speed (Rpm)	10,000	
Max. Torque	75 Ft-Lb	102
Overall Length	5-1/2"	139 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	2.5 Cfm	71 L/min.
Net Weight	0.8kgs	1.75 Lbs

**DB-I-32**



3/8" Air Impact Wrench  
(Rocking Dog Mech.)  
Max. Torque: 175Ft-Lb

Square Drive	3/8"	
Capacity (Bolt Size)	9/16/11MM	
Free Speed (Rpm)	9,500	
Max. Torque	175 Ft-Lb / 220 NM	
Overall Length	6-1/2"/165MM	
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	6 Cfm	
Net Weight	1.03kgs/2.3 Lbs	

**DB-I-35**



3/8" Air Impact Wrench  
(Single Hammer)  
Max. Torque: 200 Ft-Lb

Square Drive	3/8"	
Capacity (Bolt Size)	3/8"	M10 mm
Free Speed (Rpm)	10,000(Rpm)	
Max. Torque	135 Ft-Lb	183 N-M
Overall Length	5-1/2"	139 mm
Air Inlet (Pt/Npt)	1/4" (Pt/Npt)	
Air Hose (I.D.)	3/8" (I.D.)"	
Avg. Air Consumption	2.5 Cfm	71 L/min.
Net Weight	1.35kgs	2.97 Lbs

**DB-I-40**



1/2" Air Impact Wrench  
(One Hammer)  
Max. Torque: 230 Ft-Lb

Square Drive	1/2"	
Capacity (Bolt Size)	5/8"(inch)	M 16
Free Speed (Rpm)	7,000(Rpm)	
Max. Torque	230Ft-Lb	312 N-M
Overall Length	7"	312 mm
Air Inlet (Pt/Npt)	1/4" (Pt/Npt)	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	7 Cfm	198 L/min.
Net Weight	2.2kgs	4.8 Lbs

**DB-I-40K**



1/2" Air Impact Wrench  
Wrench Kit

- 1 Pc. I-40
- 10 Pcs. Air Sockets 9, 10, 11, 13, 14, 17, 19, 22, 24, 27
- 1 Pc. 5" Extension Bar
- 1 Pc. Oil Pot
- 1 Pc. Hex Wrench

**DB-I-44**



1/2" Heavy Duty  
Air Impact Wrench  
Max. Torque: 400 Ft

Square Drive	1/2"	
Capacity (Bolt Size)	5/8"	M16 mm
Free Speed (Rpm)	8,000 (Rpm)	
Max. Torque	500 Ft-Lb	678 Nm
Overall Length	7-1/8"	180 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	4.2 Cfm	119 L/min.
Net Weight	2.56kgs	5.58 Lbs

**DB-I-48**



1/2" Heavy Duty  
Air Impact Wrench  
(Handle Exhaust)  
Max. Torque: 600 Ft-Lb

Square Drive	1/2"	
Capacity (Bolt Size)	5/8"	M16 mm
Free Speed (Rpm)	7,000 (Rpm)	
Max. Torque	600 Ft-Lb	813 N-M
Overall Length	7-21/64"	186 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	4.2 Cfm	119 L/min.
Net Weight	2.56kgs	5.58 Lbs

**DB-I-16**



1/2" Composite Indus.  
Impact Wrench (Twin Han.)  
Max. Torque: 1,000 Ft-Lb

Square Drive	1/2"	
Capacity (Bolt Size)	5/8"	M16 mm
Free Speed (Rpm)	10,000	
Max. Torque	1,000	1,356
Overall Length	7-3/5"	193 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	13 Cfm	368 L/min.
Net Weight	2.02kgs	4.54 Lbs

POWER TOOL

**DB-I-08**

1/2" Composite Industrial Mini Air Impact Wrench (Twin Hammer)  
Max. Torque: 400 Ft-Lb



Square Drive	1/2"	
Capacity (Bolt Size)	1/2"	M13 mm
Free Speed (Rpm)	10,000	
Max. Torque	400	434/542
Overall Length	6-1/2"	165 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	6 Cfm	170 L/min.
Net Weight	1.2kgs	2.6 Lbs

**DB-I-03**

1/2" Composite Industrial (Twin Hammer) Mechanism Impact Wrench



Square Drive	1/2"	
Capacity (Bolt Size)	3/4"	M19 mm
Free Speed (Rpm)	75,00	
Max. Torque	850ft-lb	881nm
Overall Length	7-3/5"	193 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	10 Cfm	283 L/min.
Net Weight	2.1kgs	4.6 Lbs

**DB-I-05**

1/2" Composite Industrial Air Impact Wrench (Twin Hammer)  
Max. Torque: 600 Ft-Lb



Square Drive	1/2"	
Capacity (Bolt Size)	3/4"	M19
Free Speed (Rpm)	8,000	
Max. Torque	600 Ft-Lb	813 N-M
Overall Length	7-5/8"	193 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	4.4 Cfm	125 L/min.
Net Weight	2.15kgs	4.73 Lbs

**DB-I-66**

3/4" H/D Air Impact Wrench (Twin Hammer)  
Max. Torque: 750 Ft-Lb



Square Drive	3/4"	
Capacity (Bolt Size)	1"	M26
Free Speed (Rpm)	6,500	
Max. Torque	750	1,016 N-M
Overall Length	9-19/64"	236 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	7 Cfm	198 L/min.
Net Weight	4.55kg	10 Lbs

**DB-I-69**

3/4" H/D Air Impact Wrench (Twin Hammer) (Handel Exhaust)  
Max. Torque: 1250 Ft-Lb



Square Drive	3/4"	
Capacity (Bolt Size)	1-1/4"	M32
Free Speed (Rpm)	5,000 Rpm	
Max. Torque	1,250 Ft-Lb	1,695 N-M
Overall Length	8-1/2"	217 mm
Air Inlet (Pt/Npt)	3/8"	
Air Hose (I.D.)	1/2"	
Avg. Air Consumption	8 Cfm	230 L/min.
Net Weight	4.3 Kgs	9.6 Lbs

**DB-I-07**

3/4" Composite Industrial Air Impact Wrench (Twin Hammer)  
Max. Torque: 1,100 Ft-Lb



Square Drive	3/4"	
Capacity (Bolt Size)	1"	M26mm
Free Speed (Rpm)	4,500 Rpm	
Max. Torque	1,100 Ft-Lb	1,490 N-M
Overall Length	9-1/2"	240 mm
Air Inlet (Pt/Npt)	3/8"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	9.7 Cfm	275 L/min.
Net Weight	3.8kgs	8.4 Lbs

**DB-I-80P**

1" Heavy Duty Twin Hammer Mechanism Air Impact Wrench With 2" Anvil  
Max. Torque: 1,200 Ft-Lb



Square Drive	1"	
Capacity (Bolt Size)	1-17/64"	M32
Free Speed (Rpm)	5,500 Rpm	
Max. Torque	1,200 Ft-Lb	1,626N-M
Overall Length	8-53/64"	224 mm
Air Inlet (Pt/Npt)	3/8"	
Air Hose (I.D.)	1/2"	
Avg. Air Consumption	9.5 Cfm	269 L/min.
Net Weight	5.64kgs	12.41 Lbs

**DB-I-87(-6)(-8)**

1" Heavy Duty Rocking Dog Mechanism Air Impact Wrench With 2" (6") (8") Anvil  
Max. Torque: 1,200 Ft-Lb



Square Drive	1"	
Capacity (Bolt Size)	1-1/2"	M38 mm
Free Speed (Rpm)	3,500 Rpm	
Max. Torque	1,200 Ft-Lb	1,630N-M
Overall Length	17-1/2"	445 mm
Air Inlet (Pt/Npt)	3/8"	
Air Hose (I.D.)	1/2"	
Avg. Air Consumption	18 Cfm	509 L/min.
Net Weight	11.8kgs	26.0 Lbs

POWER TOOL

**DB-I-85(-6)**



1" Heavy Duty  
Twin Hammer Mechanism  
Air Impact Wrench  
With 1" (6")Anvil  
Max. Torque: 1800 Ft-Lb

Square Drive	1"	
Capacity (Bolt Size)	1-27/64"	M36 mm
Free Speed (Rpm)	4,000	
Max. Torque	FT-LB 1,800	2,439N-M
Overall Length	12-13/32"	315mm
Air Inlet (Pt/Npt)	1/2"	
Air Hose (I.D.)	1/2"	
Avg. Air Consumption	9 Cfm	255 L/min.
Net Weight	11.44kgs	25.16 Lbs

**DB-I-86(-6)**



1" Heavy Duty  
Twin Hammer Mechanism  
Air Impact Wrench  
With 2" (6") (8")Anvil  
Max. Torque: 2,200 Ft-Lb

Square Drive	1"	
Capacity (Bolt Size)	1-1/5"	M30
Free Speed (Rpm)	2,800	
Max. Torque	2,200 FT-LB	2,987 N-M
Overall Length	21-3/5"	393 mm
Air Inlet (Pt/Npt)	3/8"	
Air Hose (I.D.)	1/2"	
Avg. Air Consumption	16 Cfm	453 L/min.
Net Weight	10.3kgs	22.71 Lbs

**DB-RW-55A**

3/8"Mini Air Ratchet  
Wrench (30 Ft-Lb)



Square Drive	1/4(3/8")	
Capacity (Bolt Size)	5/16"	M8
Free Speed (Rpm)	230 Rpm	
Max. Torque	30 Ft-Lb	40 N-m
Overall Length	6-1/2"	165 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	5/16"	
Avg. Air Consumption	4 Cfm	113 L/min.
Net Weight	0.5kgs	1.1 Lbs

**DB-RW-54**

1/2"H/D Air Ratchet  
Wrench (90 Ft-Lb)



Square Drive	1/2"	
Capacity (Bolt Size)	1/2"	M13mm
Free Speed (Rpm)	150 Rpm	
Max. Torque	90 Ft-Lb	122 N-m
Overall Length	14-3/8"	365 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	6 Cfm	170 L/min.
Net Weight	2.0kgs	4.4 Lbs

**DB-RW-11/12**

Open Type Ratchet Wrench With  
Catcher (8/18 Ft. Lb)



	RW-11	RW-12
Square Drive	6,7,8,10,12	10, 11, 12, 13, 14
Capacity (Bolt Size)	1/2" M12 mm	1/2" M14
Free Speed (Rpm)	120	170 M18
Max. Torque	8 11	25 13-2/5"
Overall Length	11-4/5" 300 mm	340mm
Air Inlet (Pt/Npt)	1/4"	1/4
Air Hose (I.D.)	3/8"	3/8
Avg. Air Consumption	2 Cfm 56	2Cfm 56
Net Weight	1.3kgs 2.86 Lbs	1.8 kgs4.0Lbs

**DB-D-30**

3/8" Heavy Duty  
Air Drill



Drilling Cap.	3/8"	
Free Speed (Rpm)	2,200 Rpm	
Overall Length	6-1/2"	165 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	6 Cfm	170 L/min.
Net Weight	0.9kgs	2.0 Lbs

**DB-D-31**

3/8" Heavy Duty  
Air Drill  
Reversible Drill



Drilling Cap.	3/8"	
Free Speed (Rpm)	1,800	
Overall Length	6-1/2"	165 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	4 Cfm	113 L/min.
Net Weight	0.9kgs	2.0 Lbs

**DB-D-32**

3/8" Heavy Duty  
Air Reversible Drill



Drilling Cap.	3/8"	
Free Speed (Rpm)	1,800	
Overall Length	7"	178 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	4 Cfm	113 L/min.
Net Weight	1.36kgs	3.0 Lbs

POWER TOOL

**DB-D-05**

3/8" Heavy Duty  
Air Reversible Drill



Drilling Cap.	3/8"	
Free Speed (Rpm)	2,300	
Overall Length	8"	200 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	3 Cfm	85 L/min.
Net Weight	1.1kgs	2.4 Lbs

**DB-D-41**

1/2" Heavy Duty  
Air Reversible Drill



Drilling Cap.	1/2"	
Free Speed (Rpm)	800	
Overall Length	7"	180 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	8 Cfm	226 L/min.
Net Weight	1.1kgs	2.42 Lbs

**DB-D-35**

3/8" Heavy Duty Air Angle Drill



Drilling Cap.	3/8"	
Free Speed (Rpm)	1,900	
Overall Length	7-1/2"	190 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	5 Cfm	141 L/min.
Net Weight	0.96kgs	2.1 Lbs

**DB-D-38**

3/8" Heavy Duty Air Straight Drill  
(2600/4500 Rpm)



Drilling Cap.	3/8"	
Free Speed (Rpm)	2,600	
Overall Length	8-1/2"	216 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	6 Cfm	170 L/min.
Net Weight	0.9kgs	2.0 Lbs

**DB-D-440**

1/2 Super Duty  
Max Torque 5.6 Ft-Lb  
Air Reversible Drill



Drilling Cap.	1/2"	3/8"
Free Speed (Rpm)	150 Rpm	2,600
Overall Length	7 1/2", 190mm	6-7/10" 170mm
Air Inlet (Pt/Npt)	1/4"	1/4"
Air Hose (I.D.)	3/8"	3/8"
Avg. Air Consumption	8 Cfm 226 L/min.	6.5 Cfm 184 L/min
Net Weight	1.4kg 3.8 Lbs	1.02kgs 2.25Lbs

**DB-D-430**

3/8" Heavy Duty  
Air Reversible Drill

**DB-TP-400**

Heavy Duty Gear Driven Air Tapping Tool

**DB-TP-401**

Heavy Duty Clutch Type  
Air Tapping Tool



Tapping Capacity	6-12 Al	6-12 Co. 6-8 Iron	3-10 Al 6-12 Co. 3-8 Iron
Speed (Rpm)	150 Rpm	2500 Rpm	2500 Rpm
Overall Length	9-7/10"	245 mm	8-9/10" 245mm
Air Inlet (Pt/Npt)	1/4"	3/8"	1/4"
Air Hose (I.D.)	3/8"	3/8"	3/8"
Avg. Air Consumption	7 Cfm 198 L/min.	7Cfm 198 L/min.	3.0Lbs
Net Weight	1.9kgs 4.19 Lbs	1.36kg	

**DB-D-16/17**

16 mm/19mm Industrial 4 Gears  
Driven Reversible Drill



Drilling	5/8"(16 mm)	3/4" (19mm)
Free Speed (RPM)	1,000	1,000
Net Weight	4.6kgs 10.1 Lbs	4.6 kgs 10.1 Lbs
Overall Length	380 mm	380mm
Air Inlet (Pt/Npt)	1/4"(pt)	1/4"
Air Hose (I.D.)	3/8"(i.d.)	3/8"
Avg. Air Consumption	3 cm	85 L/min.

**DB-D-15**

16mm Industrial 4 Gears Driven  
Air Reversible Drill



Check Size	5/8"	16mm
Free Speed (Rpm)	1,100	
Air Inlet (Pt/Npt)	3/8" (Pt/Npt)	
Avg. Air Consumption	5 Cfm	
Net Weight	5.86kg	

**DB-SD-53/54**

1/4" External Type Adjustable Clutch mechanism Screwdriver  
Torque : 45-115/45-145 In-Lb



Hex. Shank Size	1/4"	
Capacity (Bolt Size)	1/4"	6 mm
Free Speed (Rpm)	1,800 Rpm	800 Rpm
Max. Torque	IN-LB 45-115N-M	5-13 45-145
Overall Length	10" 254 mm	11" 279 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	4 Cfm	113 L/min.
Net Weight	1.2 kg	25 Lbs 1.3 kg 27 Lbs

**DB-SD-50A**

1/4" Heavy Duty Clutch Type Air Screwdriver  
Max. Torque: 26.4In-Lb  
With Quick Change Retainer



Hex. Shank Size	1/4"	
Capacity (Bolt Size)	1/8"-5/32"	3-4 mm
Free Speed (Rpm)	1,700 Rpm	
Max. Torque	26.4 IN-LB	3N-M
Overall Length	9-1/4"	235 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	1/4"	
Avg. Air Consumption	3 Cfm	85 L/min.
Net Weight	0.61kgs	1.34 Lbs

**DB-SD-50AK**

1/4" Heavy Duty Clutch Type Air Screwdriver Set



- 1 Pc SD-50A
- 1 Pc Slotted Bit (5mmx50mm)
- 1 Pc Phillips Bit (No. 1x65mm)
- 2 Pcs Wrench
- 2 Pc Spring
- 1 Pc Nipple

**DB-SD-56/57**

1/4" Internal Type Adjustable Clutch Mechanism Screwdriver  
Torque: 45-115/45-145 In-Lb



	SD 56	SD 57
Hex. Shank Size	1/4"	1/4"
Capacity (Bolt Size)	1/4"	1/4" 6mm
Free Speed (Rpm)	1,800 Rpm	800 Rpm
Max. Torque (In-Lb/NM)	45-115 / 5-13	45-145/ 5-17
Overall Length	10", 254mm	11", 279mm
Air Inlet (Pt/Npt)	1/4"	1-1/4"
Air Hose (I.D.)	3/8"	3/8"
Avg. Air Consumption	4 Cfm 113 L/min.	4 Cfm 113 L/min.
Net Weight	1.1kgs 2.5Lbs	1.13kgs 2.7Lbs

**DB-SD-58/59**

1/4" External Type Adjustable Cushion Clutch Air Screwdriver

1/4" Push-To-Start-Shut-Off External Clutch Air Screwdriver



Hex. Shank Size	1/4"	1/4"
Capacity (Bolt Size)	2-3.5mm	2.5-4.0mm
Free Speed (Rpm)	1,200 Rpm	1000 Rpm
Max. Torque	2-15 Kgs/Cm	4-18 Kgs/Cm
Overall Length	220 mm	230 mm
Air Inlet (Pt/Npt)	1/4"	1/4"
Air Hose (I.D.)	1/4"	1/4"
Avg. Air Consumption	3 Cfm (85 L/min.)	
Air Pressure	90 Psi	90 Psi
Net Weight	0.62 Kgs	0.67 Kgs

**DB-SD-6SLD**

1/4" Industrial Two Hammer Mechanism Air Screwdriver



Specification:

Shank Size	: 1/4"
Capacity(Bolt Size)	: 6mm
Torque Range	: 10-18 N-M
Free Speed	: 8,000Rpm
Net Weight	: 1.2Kgs(2.4Lbs)
Overall Length	: 7"(175mm)
Air Inlet	: 1/4"(Pt)
Air Hose	: 1/4"(I.d.)
Packing	: 10/Ctn/14Kgs/1.0'

**DB-SD-51**

1/4" Heavy Duty Adjustable Clutch Type Air Screwsriver



Specification	:
Hex.Shank Size	: 1/4"
Capacity(Bolt Size)	: 5.0mm
Free Speed	: 1,900 Rpm
Max.Torque	: 5.0(N-M)
Overall Length	: 220mm
Air Inlet	: 1/4"(Pt/Npt)
Air Hose	: 1/4"(I.d)
Air Consumption	: 2 Cfm(56 L/Min.)
Net Weight	: 1.39 Lbs(0.63Kgs)
Packing	: 20/Ctn/18Kgs/1.4'

**DB-SD-104/105**

1/4" Push-Start & Shut-Off & Button Reverse Air Screwdriver



	SD-104/104B	SD-105/105B
Hex. Shank Size	1/4"	1/4"
Free Speed (Rpm)	850	500 Rpm
Torque Range 104 (B)	9.7-22.8/16.3-37.4	0.6-1.4/1-2.3
Torque Range 105 (B)	27.7-65.1/73.2-130.2	1.7-4.0/4.5-8.0
(Torque in Kg.cm)		
Overall Length	10-2/5" 265mm	11-2/5" 290mm
Air Inlet (Pt/Npt)	1/4"	1/4"
Air Hose (I.D.)	1/4"	1/4"
Avg. Air Consumption	3 Cfm 85 L/min.	3 Cfm 85 L/min.
Net Weight	0.72kgs 1.6 Lbs	0.99kgs 2.18 Lbs

**DB-SD-80/81**

1/4" Internal/External Type Adjustable Clutch Mechanism Screwdriver Torque: 45-115 In Lbs



Hex. Shank Size	1/4"	1/4"
Capacity (Bolt Size)	1/4" 6 mm	1/4" 6 mm
Free Speed (Rpm)	1,800 Rpm	800
Max. Torque (In-Lb)	45-115	45-145
Overall Length	7" 178 mm	8-1/2" 216mm
Air Inlet (Pt/Npt)	1/4"	1/4"
Air Hose (I.D.)	3/8"	3/8"
Avg. Air Consumption	6 Cfm 226 L/min.6Cfm	226L/min.
Net Weight	1.1kgs 2.5 Lbs	1.23kg 2.7Lbs

**DB-SD-60A**

1/4" Ind. Twin Hammer Mechanism Impact Screwdriver Torque: 30 Ft-Lb With Quick Retainer



Hex. Shank Size	1/4"
Capacity (Bolt Size)	5/32"-1/4" 4-6 mm
Free Speed (Rpm)	10,000 Rpm
Max. Torque	26ftlb 40 N-M
Overall Length	7" 178 mm
Air Inlet (Pt/Npt)	1/4"
Air Hose (I.D.)	1/4"
Avg. Air Consumption	3 Cfm 85 L/min.
Net Weight	0.79kgs 1.74 Lbs

**DB-SD-6SSL/6SSLD**

3/8" Sq. Industrial Two Hammer Mechanism Impact Screw Driver/Torque-148 FT-LB with 1/4" (Hex. Shank)



Hex. Shank Size	1/4"(3/8" Sq.)	1/4"(3/8" Sq.)
Capacity (Bolt Size)	5/32-1/4" 4-6 mm	1/4"-5/16" 6-8 mm
Free Speed (Rpm)	8,000 Rpm	8,300
Max. Torque	10-21 nm	10-18nm
Overall Length	8" 202 mm	8" 202mm
Air Inlet (Pt/Npt)	1/4"	1/4"
Air Hose (I.D.)	1/4"	3/8"
Avg. Air Consumption	3 Cfm 85 L/min.	4 Cfm 113 L/min
Net Weight	1kg 2.2 Lbs	1 kg 2.2 Lbs

**DB-SD-67**

1/4" Heavy Duty Angle Type Air Impact Screwdriver Max. Torque:34 Ft-Lb



Hex. Shank Size	1/4" / 3/8"dx
Capacity (Bolt Size)	3/16" 5 mm
Free Speed (Rpm)	5,000 Rpm
Max. Torque	34Ft-Lb 46 N-M
Overall Length	10-1/4" 260 mm
Air Inlet (Pt/Npt)	1/4"
Air Hose (I.D.)	1/4"
Avg. Air Consumption	8 Cfm 226 L/min.
Net Weight	1.5kgs 3.31 Lbs

**DB-SD-69**

1/4" Heavy Duty Air Impact Screwdriver Max. Torque:148 Ft-Lb



Hex. Shank Size	1/4"
Capacity (Bolt Size)	1/4" 6mm
Free Speed (Rpm)	7,500 Rpm
Max. Torque	148 Ft-Lb 200 N-M
Overall Length	7-1/2" 190 mm
Air Inlet (Pt/Npt)	1/4"
Air Hose (I.D.)	3/8"
Avg. Air Consumption	8 Cfm 226 L/min.
Net Weight	1.2kgs 2.65 Lbs

**DB-NS-505**

Air Needle Scaler



Needle Diameter Dia.xL	3x180x19mm
Piston Stroke	33 mm
Blow Per. Min. (BPM)	3,700
Air Inlet (Pt/Npt)	1/4"
Air Hose (I.D.)	3/8"
Overall Length	13" 330 mm
Air Consumption	10 Cfm 283 L/min.
Net Weight	2.7kgs 5.95 Lbs 2.8kgs 6.17 Lbs

**DB-H-14/R**

**DB-H-14/H**

4" Air Chipping Hammer



Piston Diameter	1-1/8"	28.5 mm
Piston Stroke	4"	102mm
Blow Per. Min. (BPM)	1,500	
Overall Length	16-1/8"	470mm
Air Inlet (Pt/Npt)	3/8"	
Air Hose (I.D.)	1/2"	
Air Consumption	12 Cfm	342 L/min.
Net Weight	7.0kgs	15.42 Lbs'

**DB-FC-501**

Air Flux Chipper



Needle Diameter Dia.xL	
Piston Stroke	33 mm
Blow Per. Min. (BPM)	2,700
Air Inlet (Pt/Npt)	1/4"
Air Hose (I.D.)	3/8"
Overall Length	13-1/5" 335 mm
Air Consumption	10 Cfm 283 L/min.
Net Weight	2.2kgs 4.85 Lbs

**DB-DG-33**

1/4" Mini Die Grinder  
(22000 RPM)



Collect Size	1/4"	6.0 mm
Free Speed (Rpm)	22,000 Rpm	
Overall Length	5-1/2"	140 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	4 Cfm	113 L/min.
Net Weight	0.7kgs	1.54 Lbs

**DB-DG-33(L)**

1/4" Medium Die  
Grinder (Front Exhaust)  
(25,000 Rpm)



Collect Size	1/4"	6.0 mm
Free Speed (Rpm)	25,000 Rpm	
Overall Length	5-3/4"	146 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	4 Cfm	113 L/min.
Net Weight	0.6kgs	1.17 Lbs

**DB-DG-7200**

1/4"(6mm) Industrial  
Die Grinder (25,000 RPM)



Collect Size	1/4"	6 mm
Free Speed (Rpm)	25,000 Rpm	
Overall Length	6"	153 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	3.5"	99 mm
Net Weight	0.36kgs	0.8 Lbs

**DB-DG-30**

0.3 HP 1/4"(6mm) Mini Air  
Die Grinder



Free Speed (Rpm)	28,000 Rpm	
Horse Power	0.23 KW	0.3 HP
Collect Size	1/4"	6 mm
Avg. Air Consumption	6 Cfm	
Overall Length	6-1/4"	160 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	1/4"	

**DB-DG-32(M)**

0.9 Hp 1/4"(6mm) Air Die  
Grinder



Free Speed (Rpm)	18,000 Rpm	
Horse Power	0.65 Kw	0.9 HP
Collect Size	1/4"	6 mm
Avg. Air Consumption	10 Cfm	
Overall Length	7-1/4"	184
Air Inlet (Pt/Npt)	1/4"	
Air Hose	3/8"	

**DB-DG-34(M)**

1/4" Angle Die Grinder  
(20,000 Rpm)



Capacity	1/4"	6.0mm
Free Speed (Rpm)	20,000	
Overall Length	6-5/16"	160 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	4 Cfm	113 L/min.
Net Weight	0.5kgs	1.1 Lbs

**DB-MD-70/80**

Roll Throttle Type  
Micro Grinder  
(54,000/70000 Rpm)



Capacity	1/8"	3.0 mm
Free Speed (Rpm)	54,000 Rpm / 70,000 Rpm	
Overall Length	5-1/4"	132 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	1/4"	
Avg. Air Consumption	2 Cfm	57 L/min.
Net Weight	0.2kgs	0.5 Lbs

**TG-50**

1/4" (6mm) Mini Roll Type  
Throttle Gringer  
Grinder

**TG-50L**

With Lever  
Type Throttle



Capacity (Bolt Size)	1/4"	6mm
Free Speed (Rpm)	18,000 Rpm	
Overall Length	7"	180mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	4.5 Cfm	127 L/min.
Net Weight	0.7kgs	1.55 Lbs



**DB-N-72/73**

Air Nipper



Cutting Capacity Steel	0.5mm/1.0mm
Copper	1.0mm/1.5mm
Plastic	2.0mm/4.0mm
Power (Kg-cm)	40 / 60
Avg. Air Consumption	0.06 / 0.11

**DB-NB-25(Push)/26(Pull)**

Air Nibbler



Cutting Capacity Steel	1.4mm
Aluminum	1.8 mm
Stroke Length	3,500 mm
Net Weight	0.96kgs 2.1 Lbs
Avg. Air Consumption	6 Cfm 170 L/min.

**DB-B-20**

Air Metal Shear



Cutting Capacity	1.2 mm Steel	1.4 mm Alumin.
Stroke Length	5.5 mm	
Stroke Per Minutes (B.P.M)	2,500	
Avg. Air Consumption	6 Cfm	170 L/min.
Net Weight	1.1kgs 2.32 Lbs	1.3kgs 2.8 Lbs

**DB-B-11**

Air body Saw  
(10,000 Rpm)



Cutting Capacity	2mm Steel	3mm Aluminum
Stroke Length	9.5 mm	
Stroke Per Minutes (B.P.M)	10,000	
Avg. Air Consumption	6 Cfm	170 L/min.
Net Weight	0.8kgs	1.76 Lbs

**DB-K-14**

Air Knife  
(20,000 Rpm)



Cutting Oscillations (RPM)	20,000
Cutting Distance	3 mm
Avg. Air Consumption	6 Cfm 170 L/min.
Net Weight	1.3kgs

**DB-CO-27**

3" H/D Air Cut-Off Tool  
(18,000 Rpm)



Cutting Wheel	3"
Free Speed (RPM)	18,000
Net Weight	0.8kgs
Avg. Air Consumption	6 Cfm 170 L/min.

**DB-S-37**

0.3Hp 2"Air Angle Sander



Free Speed (Rpm)	15,000
Horse Power	0.23 KW
Pad Size	2" Pad
Overall Length	6-1/2" 165 mm
Air Inlet (Pt/Npt)	1/4"
Air Hose (I.D.)	1/4"
Avg. Air Consumption	6 Cfm

**DB-AG-36G (4")/ 45G (5")**

Heavy Duty Lever  
Throttle Type angle Grinder



Capacity	4" / 5"	100mm / 125mm
Free Speed (Rpm)	11,000 / 11,000	
Overall Length	9"	230 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	6 Cfm	170 L/min.
Net Weight	1.8kgs	4.0 Lbs

POWER TOOL

**DB-AG-36**

4-1/2" Heavy Duty Lever Throttle Type angle Grinder



Capacity	4-1/2"	114mm
Free Speed (Rpm)	11,000	
Overall Length	9"	230 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	6 Cfm	170 L/min.
Net Weight	1.8kgs	4.0 Lbs

**DB-AG-7G**

7" Angle Grinder



Capacity	7"	178mm
Free Speed (Rpm)	7,000 Rpm	
Overall Length	10"	252 mm
Air Inlet (Pt/Npt)	1/2" Size	
Air Hose (I.D.)	1/2" Size	
Avg. Air Consumption	8 Cfm	226 L/min.
Net Weight	2.9kgs	6.4 Lbs

**DB-S-70/70A**

7" Vertical Sander/Polisher (2,000 Rpm)



Spindle Pad	7"	178 mm
Spindle Thread	5/8x11UNC	
Free Speed (Rpm)	2,000 (S-70) 4,000 (S-70A)	
Overall Length	7-1/2"	190 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	10 Cfm	283 L/min.
Net Weight	2.6kgs	5.7 Lbs

**DB-S-74/74A**

7" Heavy Duty Air Angle Sander/Polisher



Sanding Pad	: 7"(178mm)
Spindle Thread	: 5/8"-11UNC
Free Speed	: 2500 Rpm(S-74) 4500 Rpm(S-74A)
Overall Length	: 16"(406mm)
Air Inlet	: 1/4"(Pt/Npt)
Air Hose	: 1/2"(I.d.)
Air Consumption	: Cfm(340 L/Min)
Net Weight	: 2.0Kgs(5.3 Lbs)

**DB-S-12**

5" High Speed Sander (with Iron Safty Guard) 18,000 Rpm)



Sanding Pad	5-1/2"	140 mm
Spindle Thread	7/16"-20UNF	
Free Speed (Rpm)	18,000 Rpm	
Overall Length	8-1/4"	205 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	4 Cfm	112 L/min.
Net Weight	1.2kgs	2.64 Lbs

**DB-BS-09**

Air Belt Sander (10x330mm)



Sanding Pad	: 3/8"x13"(10 x 330mm)
Free Speed	: 16,000 Rpm
Overall Length	: 11 2/5"(290mm)
Air Inlet	: 1/4"(Pt)
Air Hoise	: 3/8"(I.d.)
Air Consumption	: 6 Cfm(171L/Min)
Net Weight	: 0.8Kgs(1.76 Lbs)

**DB-BS-10**

Air Belt Sander (7/8"X20") With Iron Pully



Sanding Pad	: 7/8"x20"(20x520mm)
Free Speed	: 16,000 Rpm
Overall Length	: 17"(430mm)
Air Inlet	: 1/4"(Pt)
Air Hose	: 3/8"(I.d.)
Air Pressure	: 90 Psi
Air Consumption	: 6 Cfm(171L/Min)
Net Weight	: 1.2Kgs(2.6 Lbs)

**DB-S-25**

Professional Air Jittburg Sander(176x93mm)



Sanding Pad	: 93X 176 mm
Free Speed	: 7,000 Rpm
Tool Length	: 210 mm
Tool Height	: 130 mm
Orbit Diameter	: 5.0mm
Air Inlet	: 1/4"(Pt/Npt)
Air Hose	: 3/8"(I.d.)
Air Consumption	: 6 Cfm
Net Weight	: 1.8 Kgs

DB-S-25V Self Vacuum Type

POWER TOOL

**DB-S-17**

Air Palm Sander  
(89x197mm)



Sanding Pad	100x110	
Free Speed (Rpm)	20,000 Rpm	
Orbit Diameter	1.6 mm	
Overall Length	5"	127 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	2 Cfm	57 L/min.
Net Weight	0.5kgs	1.1 Lbs

**DB-S-45**

Air Random Orbital Sander  
With 5" / 6" Pad (10,000 Rpm)



Orbit Diameter	3/16"	5mm
Spindle Thread	5/16"-24	
Free Speed (Rpm)	9,500 Rpm	
Overall Length	6-1/10"	155 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	6 Cfm	170 L/min.
Net Weight	1.1kgs	2.4 Lbs

**DB-S-63**

Composite  
Air Random  
Orbital Sander With 5/6"- Pad  
(10,000 Rpm)



Orbit Diameter	3/16"	5mm
Spindle Thread	5/16"-24	
Free Speed (Rpm)	10,000 Rpm	
Overall Length	10"	155 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	6 Cfm	170 L/min.
Net Weight	0.85kgs	2.0 Lbs

**DB-S-25**

Professional Air  
Jitterbug Orbital  
Sander (176x93 mm)



Sanding Pad	7"x3-7/10"	176x93 mm
Free Speed (Rpm)	7,000 Rpm	
Orbit Diameter	3/16"	5 mm
Overall Length	8-3/10"	210 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Avg. Air Consumption	6 Cfm	170
Net Weight	1.8kgs	4.0 Lbs

**DB-R-15**

Air-Hydraulic Riveter

**DB-R-15V**

Vacuum Type



Blind Rivet Setting Capacity	3/16", 5/32", 1/8", 3/32"	
Traction Power	1586 Lbs	720kgs
Stroke Length	9/16"	14 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Net Weight	1.5kgs	3.4 Lbs

**DB-R-15A**

Air-Hydraulic Riveter

**DB-R-15A(V)**

Vacuum Type



Blind Rivet Setting Capacity	3/16", 5/32", 1/8", 3/32"	
Traction Power	2000 Lbs	910kgs
Stroke Length	9/16"	14 mm
Air Inlet (Pt/Npt)	1/4"	
Air Hose (I.D.)	3/8"	
Net Weight	1.5kgs	3.4 Lbs

**DB-R-15K**



- 1PC R-15 Air Riveter
- 1PC Joint nut
- 1PC Air hose joint 1/4"
- 1PC Air hose joint 5/16"
- 10PC Rivet 3/16"
- 10PC Rivet 5/32"
- 10PC Rivet 1/8"
- 10PC Rivet 3/32"
- 1PC Oiler
- 1PC Blow case
- 1PC Jaw case
- 1PC Jaw case joint
- 1PC Jaw
- 1PC Jaw pusher
- 1PC Return Spring A
- 1PC Return spring B
- 1PC Valve pusher spring
- 1PC Jaw pusher spring

- 2PCS Nosepiece 4.8m/m(3/16")
- 2PCS Nosepiece 4.0m/m(5/32")
- 2PCS Nosepiece 3.2m/m(1/8")
- 2PCS Nosepiece 2.4m/m(3/16")
- 1PC Frame brass joint
- 1PC Frame brass joint
- 1PC Spanner gauge
- 1PC Spanner
- 2PCS Frame O ring (P12X2.4)
- 2PCS Frame back up ring (P12X1.2)
- 1PC Oil piston O ring (P22X3.5)
- 1PC Oil piston back up ring (P22x1.2)
- 1PC Frame Joint O ring (P12x2.4)
- 1PC Valve pusher O ring (P7x1.9)
- 1PC Valve pusher O ring (P6x2)
- 1PC Valve (13.5mm)
- 1PC Valve cap O ring (P12x2.4)

POWER TOOL

**DB-R-17**

9/32" Air-Hydraulic Riveter



Capacity	9/32" (7) Aluminum	9/32" (7) S.S Steel
Tracking Power		2,500Kg (5,500Lbs)
Stroke Length		23(7/8")
Air Inlet (Pt/Npt)		1/4"
Air Hose (I.D.)		3/8"
Overall Length (mm/inc)		400 (15-3/4")
Net Weight Kgs (Lbs)		3.8 Kgs (8 Lbs)

**DB-R-6100V**

3/16" Composite Self Vacuum Type Air Hydraulic Riviter



Blind Rivet Capacity	3/16", 5/32", 1/8", 3/32"
Traction Power	1000 kg
Stroke Length	16 mm
Air Consumption	0.03kg
Weight	1.5 Cfm
Air inlet	1/4"

**DB-R-03V**

1/4" Composite Self Vacuum Type Air Hydraulic Rivetes



Blind Rivet Capacity	1/4", 3/16", 5/32" 1/8"
Traction Power	1700 kg
Stroke Length	23 mm
Air Consumption	0.05kg
Weight	2.4 Cfm
Air inlet	1/4"

**PS-1001/1002**

Air Pull Setter



	PS-1001	PS-1002
Capacity	M-3/4/5/6	M-6/8/10
Free Speed (Rpm)	350	450
Weight	1.3 kg	1.7kg
Air Consumption	5	3
Air Hose Size	3/8	7/5
Air inlet	1/4"	1/4"

**DB-AN-C55**

Heavy Duty Coil Nailer



Tool Length	: 290 mm
Width	: 130 mm
Height	: 270 mm
Weight	: 2.8 kgs
Load Capacity	: 300 Nails
Working Pressure	: 4-7 kgs/cm2 (60-100psi)

**DB-AN-C70**

Heavy Duty Coil Framing Nailer



Tool Length	: 315mm
Width	: 130 mm
Height	: 325 mm
Load Capacity	: 300 Nails
Working Pressure	: 4-7 kgs/cm2 (60-100 psi)

**DB-AN-8016**

Pneumatic Stapler



<b>Application Fasteners Size/Tool Specification</b>			
Application : Furniture, Wood Box & Shoe Manf,			
Crown	12.8	Weight	0.96 kg
Width	0.95	Height	147 mm
Thickness	0.65	Width	47 mm
Gauge	21	Length	230 mm
Length	6-16 mm		

**DB-AN-1650 (GAUG BRAD NAILER)**

Heavy Duty Wire Nailer



Nail Gauge	16
Nail Shank	1.6 x 14 mm
Nail Length	20 to 50 mm
Total Length	310 mm
Width	77 mm
Height	270 mm
Weight	2.18 Kg
Load Capacity	100 pcs

**DB-AN-422J**

Pneumatic Stapler



**Application Fasteners Size/Tool Specification**

Application : Furniture, Wood Box & Shoe Manf,

Crown	5.2	Weight	2.65 kg
Width	1.20	Height	295 mm
Thickness	0.60	Width	87 mm
Gauge	21	Length	380 mm
Length	13-22 mm	Load Capacity	150 Nails

**DB-AN-16851**

Heavy Duty  
Pneumatic Stapler



**Application Fasteners Size/Tool Specification**

Application : Creates, Pallets, Wooden Frames etc.

Crown	11.1	Weight	2.65 kgs
Width	1.60	Height	295 mm
Thickness	1.40	Width	87 mm
Gauge	16	Length	380 mm
Length	25-50 mm (1-2")		
Load Capacity	150 Nails		

**DB-CS-18/19/22**

Air Drive  
Carton Stapler



**Application : Corogated Box Packing**

Efficient  
Saving Energy  
Easy to Operate & Hand Carry  
The Tightness & Penetration Depth is adjustable

Length	330 mm	Model	Nail Crown	Nail Length
Width	115 mm	CS19	35 mm	16-19 mm
Height	220 mm	CS22	35 mm	18-22 mm
Weight	1.7 kgs	CS18	32 mm	15-18 mm
Load Capacity	100 Nails-3519		120 Nails-3218	

**DB-AN-1832/1850**

18G Wire Finish Nailer



**Application**

Staircases, Paneling, Interior Finish & Trimm,  
Customs Cabinets, Mouldings & Crafts

Tool Specification	AN-1832	AN-1850
Length	235 mm	205 mm
Width	55 mm	55 mm
Height	197 mm	240 mm
Weight	1.20 kg	1.40 kg
Load Capacity	100 Nails	100 Nails
Nail Length	10-32 mm	15-50 mm

**DB-HP-621**

Headless Pinner



**Application:**

Moulding, Glazings/Strips, Furnitured cabinets

Tool Specification	Nails(mm)	
Length	225 mm	L 12-20 mm
Width	45 mm	BWG 23
Height	152 mm	ST 0.64 MM
Weight	1 kg	Gauge 23 (BWG)
Load Capacity	200 Nails	

\*L-Length, SW-shank width, ST-Shank Thickness

**DB-FS-2150**

2 in 1 Nailer for  
Brad & Staple



**Application**

Staircases, Paneling, Interior Finish & Trimm,  
Customs Cabinets, Mouldings & Crafts

Tool Specification	Nails(mm)	Staples(mm)
Weight	2.64lbs	L 15-50
Height	190 mm	SW 1.25
Width	50 mm	ST 1
Length	200 mm	Gauge 18
Air Pressure	60-100 Psi	Crown 5.8
Nail Capacity	100 Pcs.	

\*L-Length, SW-shank width, ST-Shank Thickness

**DB-AN-C1(80)/C2(80)**

Air C-ring tool Short / Long Nose Type



Working Pressure	80-105 p.s.i (5-7bar)
Magazine Capacity	100pcs
Air Inlet	1/4"
Air Hose	3/8"
Length	332mm
Net Weight	1.5kg

**Fasteners Size**

Wire Dia	1.8mm (15gauge)
Shank Height	12mm
Crown	23.7mm
Closure Dia	8-8.5mm

**Application**

Idea for Spring Car Seat, Spring Mattress, Wire Cage, Wine fence, or any wire to cable applications.

**DB-H-10/R**

150 mm air Hammer With  
4Pcs 5" Chisels

**DB-H-20/R**

190 mm Air Hammer Hit  
4Pcs 5" chisels

**DB-H-30/R**

230 mm Air Hammer with  
4Pcs 5" Chisels



POWER TOOL

**TD-2600**

Industrial Concrete Breaker



Chisel Shank	26 mm
Blow Per. Min. Bpm	1,300
Piston Diameter	350 mm (1-19/50")
Piston Stroke	151(6") 6"
Net Weight	14.1Kgs 31.7 Lbs
Overall Length	438 mm 17/1/4"
Air Inlet (Pt/Npt)	1/2"
Air Hose (I.D.)	3/4"
Air Consumption	35 Cfm 991 L/min.

**DB-SG-02**

Air Spray Gun With 600cc Nylon Cup & 1.4mm Nozzle



Standard Nozzle	1.4
Optional Nozzle	1.3, 1.5, 1.7, 2.0, 2.5
Capacity of cup (cc)	600mm
Air Inlet (Ps/Nps)	1/4"
Fluid Inlet (Ps/Nps)	16x1.5"
Avg. Air Consumption	7 Cfm 200 L/min.
Working pressure (Psi)	30-45
Gun Weight	0.63 kgs 1.38 Lbs

**DB-SG-40**

Air Spray Gun With 1000cc Cup & 2.0mm Nozzle



Standard Nozzle	1.6
Optional Nozzle	1.0, 1.5, 1.8, 2.0 mm
Capacity of cup (cc)	1,000
Air Inlet (Ps/Nps)	1/4"
Fluid Inlet (Ps/Nps)	3/8"
Avg. Air Consumption	12.7 cfm 360 L/min.
Working pressure (Psi)	50-70
Gun Weight	0.8 kgs 1.76 Lbs

**DB-SG-04**

Air Spray Gun



Standard Nozzle	1.4
Optional Nozzle	1.3, 1.5, 1.7, 2.0mm
Capacity of cup (cc)	600
Air Inlet (Ps/Nps)	1/4"
Fluid Inlet (Ps/Nps)	M16x1.5
Avg. Air Consumption	7 Cfm 200 L/min.
Working pressure (Psi)	15-28
Gun Weight	0.62kgs 1.37 Lbs

**DB-SG-72/41HVLP**

HVLP Air Spray Gun



Standard Nozzle	1.6	1.6
Optional Nozzle	1.0, 1.4, 2.0mm	1.0, 1.4, 1.8
Capacity of cup (cc)	1,000	1,000
Air Inlet (Ps/Nps)	1/4"	1/4"
Fluid Inlet (Ps/Nps)	3/8"	3/8"
Avg. Air Consumption	9.2 Cfm 260 L/min.	12 Cfm 340 L/min.
Working pressure (Psi)	15-28	50-70
Gun Weight	0.52kgs 1.14 Lbs	0.62kgs 1.37Lbs

**DB-PG-04**



Body length	145mm
Nozzle	0.3mm
Cup capacity	7cc
Color Cup	Fix-on Type
Control	Push-button Ideal for general purpose, from wide spray Range of fine lines to Broad Area with use of dyes, links, Dissolved Acrylics And/or Gouaches.
Operating air pressure	1kg/cm <sup>2</sup> -(14-70PSI)-5 Kg/cm <sup>2</sup>
Excellent for photo-retouching, Technical & Medical Illustrations, Precise model markings, fine hobby crafts, etc.	

**DB-WG-55**

Air Wonder Gun



**DB-SS-03 / SS-04(Inch)**



DB-SS-03 MM		DB-SS-03 (Inch)	
P.N.O	Size (mm)	P.N.O	Size (Inch)
313010	10	393010	5/16"
313011	11	393012	3/8
313012	12	393014	7/16"
313013	13	393016	1/2"
313014	14	393018	5/8"
313016	16	393020	9/16"
313017	17	393022	5/8"
313019	19	393024	11/16"

**DB-BG-6002**  
Air Sanding Blaster Gun



**DB-AB-5010**  
4" (Length)  
**DB-AB-5010L**  
10" (Length)  
Air Blow Gun



**DB-DG-12**  
Composite Body Air Duster Gun  
with 2Pcs Needleless



**DB-SB-03** Spring Balancer  
(0.6-1.5 kgs)  
**DB-SB-04**  
(1.5-3.0 kgs)  
**DB-SB-07**  
(3.0-5.0 kgs)



**DG-10-10**  
12mm  
**DG-10-101**  
50mm  
**DG-10-102**  
80mm  
Air Dusturs



**TA-2034FRL**  
Air Control Unit



Range of Pressure 0.5~9.9 kg/cm<sup>2</sup>  
Filter Screen micro(U) 20  
Min. Dropped Flow 1,750 NL/MIN  
Ambient Temperature 5~50°c  
Lubricating Method Sprzyng 15 ML/MIN.  
Useable Oil VG-32 or OM-300A  
Lubricator Capacity (c.c) 125

**TA-3040A(1/4")**  
Mini Oiler



Mini Oiler

**DB-CG-40**  
Air Caulking Gun



(Metal Body)  
(Tube Size : 51x210 mm)

**Sanding 6" Pads**

Available in  
2"/3"/4"/5"/6"

**DB-HR-05**  
Hose Spring  
Balancer



**Polyurethane Re-coil Hose**



Hose Size 8x1x10M"  
(LxWxH)mm 305x140x370mm  
Inlet/Outlet 1/4 mm  
"Maz. Pressure 300 psi  
Net Weight/pc 5.5 Kg  
Hose Capacity 30ft(9M)  
Length/I.D./Material 5/16"/PU Braid

Model No.	Tube Size (I.D.xO.D)	W.P	B.P. (M/M)	Coil-O (PT/NPT)	Fitting	Hose Length
TA-PU5080	5x8 m/m	7bar	28bar	35	1/4	4,5,6,10,12,15(M)
TA-PU6510	6.5x10m/m	7bar	28bar	50	1/4	4,5,6,10,12,15(M)
TA-PU8012	8x12m/m	7bar	28bar	60	1/4,3/8	4,5,6,10,12,15(M)

POWER TOOL

**DB-B-36**

Air Grease Gun (400 cc)

Specification:

- Capacity : 400cc(14 Oz)
- Air Inlet : 1/4"(Pt/Npt)
- Air Hose : 1/4"(I.d.)
- Net Weight : 3.3 Lbs(1.6 Kgs)
- Packing(Kgs):10/Ctn/18.4/2.6'



**DB-B-36-6**

500 CC Air Grease Gun With 6 Pcs Accessories

Contents:

- 1 Pc TB-6036L
- 1 Pc HANDLE
- 1 Pc RIBBER TUBE
- 1 Pc ALUMINUM TUBE
- 1 Pc QUICK COUPLER
- 1 Pc CONNECTOR



**THB HOSE COUPLERS**



SHA



PHA



SFA

<b>20SHA</b>	<b>5/16"(HOSE)</b>	<b>20PHA</b>	<b>5/16"(HOSE)</b>
<b>30SHA</b>	<b>3/8"(HOSE)</b>	<b>30PHA</b>	<b>3/8"(HOSE)</b>
<b>40SHA</b>	<b>1/2"(HOSE)</b>	<b>40PHA</b>	<b>1/2"(HOSE)</b>
<b>20SFA</b>	<b>1/4"(PT)</b>	<b>20PFA</b>	<b>1/4"(PT)</b>
<b>30SFA</b>	<b>3/8"(PT)</b>	<b>30PFA</b>	<b>3/8"(PT)</b>
<b>40SFA</b>	<b>1/2"(PT)</b>	<b>40PFA</b>	<b>1/2"(PT)</b>
<b>20SMA</b>	<b>1/4"(PT)</b>	<b>20PPA</b>	<b>5x8 mm</b>
<b>30SMA</b>	<b>3/8"(PT)</b>	<b>30PPA</b>	<b>6.5x10mm</b>
<b>40SMA</b>	<b>1/2"(PT)</b>	<b>40PPA</b>	<b>8x12 mm</b>
<b>20SPA</b>	<b>5x8mm</b>	<b>20PMA</b>	<b>1/4"(PT)</b>
<b>30SPA</b>	<b>6.5x10mm</b>	<b>30PMA</b>	<b>3/8"(PT)</b>
<b>40SPA</b>	<b>8x12mm</b>	<b>40PMA</b>	<b>1/2"(PT)</b>



PFA



SMA



PPA



SPA



PMA

**THB HIGH FLOW QUICK COUPLERS**



400 PHA

- 400 PHA 1/2"(HOSE)
- 600 PHA 3/4"(HOSE)
- 800 PHA 1"(HOSE)

**THB MULTI COUPLERS**

- MATERIAL BODY : Aluminum
- WORKING PRESSURE 10~15 kgf/cm<sup>2</sup>
- MAXIMUM PRESSURE 15~20 kgf/cm<sup>2</sup>
- TEMP. RANGE -20℃~+80℃
- SIZE 1/4"(20TYPE)
- SIZE 1/4"(20TYPE), 3/8"(30TYPE), 1/2"(40TYPE)



**Insert bits (1/4" Hex Drive)**

**Slotted Bits**

- 3.0x25 mm
- 4.0x25 mm
- 5.0x25 mm
- 6.0x25 mm
- 7.0x25 mm
- 8.0x25 mm

**Philips Head Bits**

- PH-0x25 mm
- PH-1x25 mm
- PH-2x25 mm
- PH-3x25 mm

**Torx Bits**

- T 7x25 mm
- T 8x25 mm
- T 9x25 mm
- T 10x25 mm
- T 15x25 mm
- T 20x25 mm
- T 25x25 mm
- T 30x25 mm



**Insert bits / Power Bits (1/4" Hex Drive)**

**Slotted Bits**

- 3.0x50 mm
- 3.0x75 mm
- 3.0x100 mm
- 4.0x50 mm
- 4.0x75 mm
- 4.0x100 mm
- 5.0x50 mm
- 5.0x75 mm
- 5.0x100 mm
- 6.0x50 mm
- 6.0x75 mm
- 6.0x100 mm

**Philips Head Bits**

- PH-0x50 mm
- PH-0x75 mm
- PH-1x50 mm
- PH-1x75 mm
- PH-1x100 mm
- PH-1x150 mm
- PH-2x50 mm
- PH-2x175 mm
- PH-2x100 mm
- PH-2x150 mm
- PH-3x75 mm
- PH-3x100 mm

**Torx Bits**

- T 8x50 mm
- T 8x150 mm
- T 10x75 mm
- T 10x150 mm
- T 15x65 mm
- T 20x65 mm
- T 25x65 mm
- T 27x65 mm

**Pozi Drive**

- Pz1X 75
- Pz1X100 3.0x100 mm
- Pz2X 75
- Pz3X 75



**Double Ended bits (1/4" Hex Drive)**

**Philips Head Bits Double Ended Size (mm)**

- PH-1x50 mm
- PH-1x75 / 100 mm
- PH-2x75 / 100 / 150 mm
- PH-2x200 / 250 / 300 mm
- PH-3x75 / 100 mm

**Pozi Drive Double Ended Bit Size (mm)**

- Pz-1x45 mm
- Pz-1x65 mm
- Pz-2x45 mm
- Pz-2x65 mm
- Pz-3x65 mm

**Nut Driver Magnetic & Non Magnetic Size (mm)**

- 5mm x 65mm
- 5.5mm x 65mm
- 6mm x 65mm
- 7mm x 65mm
- 8mm x 65 / 100 / 150 / 200mm
- 10mm x 65 / 100 / 150 / 200mm
- 11mm x 65 / 100 / 150 / 200mm
- 12mm x 65 / 100 / 150 / 200mm
- 14mm x 65mm
- 17mm x 65mm